

ELECTRIC POKERS

Applications:

- Concrete vibration
- Low to high slump concrete
- Floors, slabs, pillars, columns, walls

Features:

- Low voltage 42V-3-200Hz
- Protected against overheating
- Vibration reduced pistol grip handles
- Oil lubrication

Advantages:

- Several diameters from Ø28mm up to 90mm
- Several pokers can be used on one frequency converter

Options:

- Longer hose
- Elastomer end-cap

Accessories:

- Extension cords see P/N page 52
- Coverage of 15m (10m of cable and 5m of hose)
- Radius of action = 10 x diameter



Electric Poker Vibrators

AX Pokers	AX36	AX40	AX48	
Tube diameter	mm	38	40	48
Tube length	mm	322	320	350
Tube weight	kg	2,2	2,3	4,2
Cable length	m	10	10	10
Voltage	V/Hz	42-3-200	42-3-200	42-3-200
Frequency	vpm	12000	12000	12000
Ampere at 42V	A	6,2	4,5	10
Vibration value	m/s ²	3,8	3,8	3,5
Noise level	dB(A)	70	78	76
Part number	4812 0508 27 4812 0508 28 4812 0508 29			

AX Pokers	AX56	AX65	AX90	
Tube diameter	mm	56	65	90
Tube length	mm	380	410	566
Tube weight	kg	5.2	7.9	18
Cable length	m	10	10	15
Voltage	V/Hz	42-3-200	42-3-20C	42-3-200
Frequency	vpm	12000	12000	6000
Ampere at 42V	A	11,7	19	21
Vibration value	m/s ²	3,7	4,6	5,0
Noise level	dB(A)	79	79	76
Part number	4812 0508 30 4812 0508 31 4812 0508 79			



CONCRETE EQUIPMENT



Electric Poker Vibrators

Devibrated handle

AX-E Pokers	AX28E	AX40E	AX48E	AX56E	
Tube diameter	mm	28/40	40	48	56
Tube length	mm	239/211	320	350	380
Tube weight	kg	2,4	2,1	4,1	5,1
Frequency	vpm	12000	12000	12000	12000
Ampere at 42V	A	4	4,5	10	11,5
Vibration value	m/s ²	0,6	0,6	0,5	0,5
Noise level	dB(A)	85	75	80	83
Part number	4812 0508 44 4812 0508 40 4812 0508 41 4812 0508 42				